



KNAUFCEILING
Solutions

DATASHEET

HERADESIGN® Fine Plus



HERADESIGN® Fine Plus is a two layer, magnesite bonded, wood wool acoustic ceiling and wall panel.

- Two-layer acoustic panel as a composite product with mineral wool absorber
- Provides trickle protection
- Excellent sound absorption values

[KNAUFCEILINGSOLUTIONS.COM](https://www.knaufceiling.com)

YOUR **CEILING**
OUR **SOLUTIONS**

System	B2.1, B2.2		C2.1																																																					
Edge details																																																								
Dimensions (mm)	1200 x 600																																																							
Thickness (mm)	40	50	65																																																					
	15/25	25/25	25/40																																																					
Weight (kg/m²)	10.5	15.6	16.9																																																					
Sound absorption	<table border="1"> <thead> <tr> <th>Thickness (mm)</th> <th>TCH (mm)</th> <th>HERADESIGN® (mm)</th> <th>Acoustic lining (kg/m²)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> <th>NRC</th> <th>Entire range α_w</th> <th>Class</th> </tr> </thead> <tbody> <tr> <td>15</td> <td>225</td> <td>25</td> <td>90</td> <td>0.60</td> <td>0.90</td> <td>0.85</td> <td>0.75</td> <td>0.70</td> <td>0.85</td> <td>0.80</td> <td>0.75 (L)</td> <td>C</td> </tr> <tr> <td>25</td> <td>225</td> <td>25</td> <td>90</td> <td>0.60</td> <td>0.90</td> <td>0.90</td> <td>0.80</td> <td>0.80</td> <td>0.90</td> <td>0.85</td> <td>0.85 (L)</td> <td>B</td> </tr> <tr> <td>25</td> <td>225</td> <td>40</td> <td>90</td> <td>0.60</td> <td>0.85</td> <td>0.90</td> <td>0.80</td> <td>0.80</td> <td>0.85</td> <td>0.85</td> <td>0.85 (L)</td> <td>B</td> </tr> </tbody> </table>	Thickness (mm)	TCH (mm)	HERADESIGN® (mm)	Acoustic lining (kg/m²)	125	250	500	1000	2000	4000	NRC	Entire range α _w	Class	15	225	25	90	0.60	0.90	0.85	0.75	0.70	0.85	0.80	0.75 (L)	C	25	225	25	90	0.60	0.90	0.90	0.80	0.80	0.90	0.85	0.85 (L)	B	25	225	40	90	0.60	0.85	0.90	0.80	0.80	0.85	0.85	0.85 (L)	B			
Thickness (mm)	TCH (mm)	HERADESIGN® (mm)	Acoustic lining (kg/m²)	125	250	500	1000	2000	4000	NRC	Entire range α _w	Class																																												
15	225	25	90	0.60	0.90	0.85	0.75	0.70	0.85	0.80	0.75 (L)	C																																												
25	225	25	90	0.60	0.90	0.90	0.80	0.80	0.90	0.85	0.85 (L)	B																																												
25	225	40	90	0.60	0.85	0.90	0.80	0.80	0.85	0.85	0.85 (L)	B																																												
Reaction to Fire	Euroclass B-s1,d0																																																							
Thermal conductivity	15/25 0.80 m²K/W	25/25 0.90 m²K/W	25/40 1.30 m²K/W																																																					
Humidity resistance	Suitable for rooms with a constant humidity of up to 90%.																																																							
Application areas	A decorative and acoustically effective suspended ceiling and wall panel for use in interior spaces as well as roofed outdoor areas that are not directly exposed to environmental influences such as rain or pollutants.																																																							
Installation	The installation of HERADESIGN® acoustic panels should take place during the last phase of the job, and in temperature and humidity controlled conditions. All building activities which create dust must be completed before the start of installation. Store the panels flat and protect against moisture and dirt. The packaging does not protect the products against rain. HERADESIGN® products should be installed in strict accordance with Knauf Ceiling Solutions installation and storage guidelines.																																																							
Designation code	WW-EN 13168-L4W2-T2-S2-P2,TR5-CI3																																																							
Special information	<ul style="list-style-type: none"> • Manufacturing tolerances in nominal dimensions: L4, W2, T2: ± 1 mm, for lengths > 1250mm L4: ± 2mm • Maximum changes in dimension in standard climate 23° C/50 % relative humidity: ± 1 ‰ 																																																							
Cleanability																																																								
Colours	Standard colours White Similar to RAL 9010 Beige Natural tone 13	vd Vario Design colours Granite Steel Green Marble Copper Oak Brass Sandstone Concrete <ul style="list-style-type: none"> • Other colours from popular RAL and NCS colour systems are available. • Deviations in colour and visual appearance may occur due to the rough fibre and panel surface. 																																																						
Sustainability																																																								

Products may vary from country to country. Please contact your local sales representative. For further information and legal notice, please visit our website.