



KNAUFCEILING
Solutions

DATASHEET

HERADESIGN[®]
Superfine A2



HERADESIGN[®] Superfine A2 is an acoustic ceiling and wall panel that provides increased fire resistance. Non-combustible wood wool acoustic panel with reaction to fire according to DIN-EN 13501-1: A2-s1, d0

- Excellent acoustic performance
- Building biology recommended

System	A2.1, A2.2		B2.1, B2.2				C2.1	S2.1						
Edge details * <small>* not all combinations edge/board thickness are available</small>		GK	AK-02/5	AK-03	SK-04	SY-02								
		AK-00	AK-02/10		SK-05									
		AK-01	AK-02/20		SK-06									
Dimensions (mm)	600 x 600, 625 x 625, 1200 x 600, 1250 x 625, additional sizes on request.													
Thickness (mm)	15, 25													
Weight (kg/m²)	12.0 (15mm), 18.0 (25mm)													
Sound absorption	Thickness (mm)	TCH (mm)	HERADESIGN® (mm)	Acoustic lining (kg/m²)	Frequencies (Hz), α_p						Entire range α_w		Class	
	25	55	0	0	125	250	500	1000	2000	4000	NRC	α_w	D	
	25	55	25	90	0.10	0.20	0.55	0.85	0.65	0.80	0.55	0.50 (MH)	B	
	25	200	0	0	0.15	0.60	1.00	0.95	0.80	1.00	0.90	0.85 (H)	C	
	25	200	25	90	0.35	0.75	0.70	0.55	0.70	0.85	0.65	0.65 (LH)	A	
Ball impact safety	Ball impact resistant according to DIN 18 032 / part 3 or class 1A according to EN 13964 annex D, Ball impact resistant for panel thicknesses ≥ 25mm <ul style="list-style-type: none"> • Ceiling panelling system B2.1, B2.2, C2.1 • Wall panelling system B2.1, B2.2, S2.1 													
Fire resistance class	EI 30 ($\alpha \leftarrow b$): detailed structure according to usability certificate													
Reaction to Fire	Euroclass A2-s1,d0													
Thermal conductivity	$\lambda = 0.10$ W/mK according to EN 12667													
Humidity resistance	Suitable for rooms with a constant humidity of up to 90%.													
Application areas	A decorative and acoustically effective suspended ceiling and wall panel for use in interior spaces as well as roofed outdoor areas that are not directly exposed to environmental influences such as rain or pollutants.													
Installation	The installation of HERADESIGN® acoustic panels should take place during the last phase of the job, and in temperature and humidity controlled conditions. All building activities which create dust must be completed before the start of installation. Store the panels flat and protect against moisture and dirt. The packaging does not protect the products against rain. HERADESIGN® products should be installed in strict accordance with Knauf Ceiling Solutions installation and storage guidelines.													
Designation code	WW-EN 13168-L4-W2-T2-S2-P2-CI3													
Special information	<ul style="list-style-type: none"> • Manufacturing tolerances in nominal dimensions: L4, W2, T2: ± 1 mm, for lengths > 1250mm L4: ± 2mm • Maximum changes in dimension in standard climate 23° C/50 % relative humidity: ± 1‰ 													
Cleanability														
Colours	Standard colours			Vario Design colours										
	White Similar to RAL 9010	Beige Natural tone 13		Granite	Steel	Green Marble	Copper	Oak	Brass	Sandstone	Concrete			
	<ul style="list-style-type: none"> • Other colours from popular RAL and NCS colour systems are available. • Deviations in colour and visual appearance may occur due to the rough fibre and panel surface. 													
Sustainability														

Products may vary from country to country. Please contact your local sales representative. For further information and legal notice, please visit our website.